



Vehicle description

Vehicle Standard data

Variant description	TGS 33.440 6X4 BB
Basic vehicle Number	L26SLG12
Emission class	EURO5
Vehicle type	Platform truck and chassis
Cab	M Cab
wheelbase	4500 mm
Overhang	2500 mm
Steering layout	Left

Permissible Weight

	Permissible weight *	techn. perm. Weights
Total weight	26000 Kg	33000 Kg
Perm. Total weight	40000 Kg	44000 Kg
Front axle	9000 Kg	9000 Kg
Rear axle	9500 Kg	13000 Kg
Rear axle 2	9500 Kg	13000 Kg

* Permissible weight is only specified if differences are desired for the technically permissible weight



Configuration for: TGS 33.440 6X4 BB / L26SLG12

Explanation: ✓ = Equipment

Engine Cooling System Clutch

- ✓ Engine D2066LF40 - 440 hp / 324 KW EURO5 SCR - (018JA)
2100 Nm C-R OBD2
- ✓ radiator and intercooler for up to 35 degrees ambient temperature (027AN)
- ✓ visco fan (116AE)
- ✓ EDC engine regulation (118MA)
- ✓ fuel filter (124AL)
- ✓ additional fuel filter with water trap, make SEPAR (124AM)
- ✓ fuel filter heating (124EA)
- ✓ control module for external data exchange (KSM) with body functions (203ER)
- ✓ air compressor 1-cylinder, 360 ccm (205AN)
- ✓ regulated rocker arm brake (EVBeC) (208AL)
- ✓ flame starting system (210AA)
- ✓ single-disc clutch MFZ 430 reinforced (211FT)
- ✓ Fly mesh guard before radiator (280EC)
- ✓ Engine start/stop device under front panel (280HD)
- ✓ Electronic speed limiter 89 km/h + 1km/h tolerance (345AU)
- ✓ Cruise control (345EA)
- ✓ COP document (542BC)
- ✓ exhaust gas certificate Euronorm (542BK)
- ✓ CEMT 5 certification (542BW)
- ✓ National registration documentation Germany (542DH)
- ✓ anti-noise package 80 dB (92/97EEC) (542FC)
- ✓ confirmation for international registration (542IZ)

Intake / Exhaust System

- ✓ air intake upswept with dry air filter / precleaner (201AR)
- ✓ exhaust upswept right (206AP)
- ✓ elbow for upswept or raised exhaust (206TA)

Gearbox

- ✓ gearbox ZF 16 S 222 OD (022GC)

Power Take-Offs

- ✓ PTO NH/1C without flange f=0.91/1.09 right side, horizontal (122QH)



Front Axle / Front Springs / Front Axle Load

- ✓ front axle VO-09 straight (025MK)
- ✓ front springs parabolic 9,5 t (026EF)
- ✓ medium-height design (281AB)
- ✓ Stabiliser for front axle (363AA)
- ✓ Reinforced shock absorber for front axle (366CA)

Rear Axle / Rear Springs / Rear Axle Load

- ✓ rear springs parabolic 13 t (028EC)
- ✓ Fit tandem axles (028PA)
- ✓ hub-reduction rear axle HPD-1382/ HP-1352 (034MH)
- ✓ with differential lock in rear axle (037AC)
- ✓ rear axle breather upswept (227AC)
- ✓ Stabiliser on both rear axles (362AH)

Transmission ratios

- ✓ planetary axle ratio $i = 3.63$ (035KK)

Rims

- ✓ disc wheels 10 hole 11.75-22.5 on 1st FA TL (038GH)
- ✓ disc wheels 10-hole 9.00-22.5 on 1st RA TL (038PG)
- ✓ disc wheels 10-hole 9.00-22.5 on 2nd RA TL (038RG)
- ✓ disc wheel 10-hole 9.00-22.5 as spare wheel TL (038TG)
- ✓ spare-wheel holder on left side (245AE)

Tyres

- Front axle ✓ 2 * 81#R0000762 WA 385/65R22,5 LENK-S+G TL 160 K Strg-S + G
- Rear axle ✓ 4 * 81#R0000744 WA 315/80R22,5 ANTR-S+G TL 154/150 K Drive-S + G
- Rear axle 2 ✓ 4 * 81#R0000744 WA 315/80R22,5 ANTR-S+G TL 154/150 K Drive-S + G
- Spare tyre ✓ 1 * 81#R0000744 WA 315/80R22,5 ANTR-S+G TL 154/150 K Drive-S + G

Fuel Tanks

- ✓ Fuel tank 400l right and 35l AdBlue (023JD)
- ✓ fuel tank fitted (03KAA)
- ✓ Lockable tank cap, 1 pc., without vent, for uniform locks (303AB)
- ✓ AdBlue filler cap 1 pc. (303CA)

Steering

- ✓ steering arrangement, left (001AA)



	✓ steering wheel with height and inclination adjustment	(030EE)
	✓ steering wheel lock with immobiliser	(256AF)
Frame	✓ Wheelbase 4500+1400 mm	(005OU)
	✓ rear frame overhang 2500 mm	(006PK)
	✓ rear underride guard, roand	(230AH)
	✓ lateral guard	(230FC)
	✓ Without front underride guard	(230XW)
	✓ 3-part steel bumper	(233EM)
	✓ cross member for trailer coupling	(236AF)
	✓ vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body	(798WK)
Trailer/Fifth-wheel Coupling	✓ trailer coupling ROCKINGER 400G150A	(234KP)
Brake System	✓ MAN BrakeMatic (electronic brake system)	(032AB)
	✓ anti-lock braking system (ABS)	(258HA)
	✓ drum brake for front axle	(259CC)
	✓ drum brake for rear axle	(259CE)
	✓ brake connection 2-line	(262AC)
	✓ asbestos-free brake linings	(263AF)
	✓ Air dryer	(370CM)
Cab exterior	✓ M cab 2240mm wide, 1880mm long	(050NN)
	✓ front panel unlockable from inside	(05NAE)
	✓ Entry lighting for driver and co-driver	(272FA)
	✓ Cab mounts on coil springs for 'M' cab	(283FB)
	✓ Central locking	(321EC)
	✓ Windscreen of laminated glass tinted	(380AC)
	✓ Door windows tinted	(380CA)
	✓ Cab rear wall without windows	(381AA)
	✓ Side windows tinted behind B-post	(385AT)
	✓ Mechanical sliding roof	(386AS)
	✓ Kerb mirror, right, heated and electrically adjustable	(392AR)
	✓ EU front mirror on co-driver's side	(392CL)
	✓ Electrically heated and adjustable rear and wide-angle mirrors	(392CY)
	✓ Mirror brackets for body width 2500-2600 mm width 2500 mm	(392HA)



	✓ spray reducer	(404AP)
Cab interior	✓ seat coverings in standard quality	(058BA)
	✓ driver's seat, high-comfort, with air suspension	(058NH)
	✓ co-driver's seat static, with longitudinal + seat back adjustment	(059NA)
	✓ door interior panelling fabric	(080AF)
	✓ air conditioning system AC R134A with automatic temperature control without CFHC	(153KC)
	✓ fine dust and pollen filter	(201FA)
	✓ Armrests for driver's seat	(276AC)
	✓ reading lamp for driver	(319AR)
	✓ Without all-roand curtain for C/M cab	(381YA)
	✓ Safety belt display, driver's side	(384CD)
	✓ Electric door window lifters for driver and co-driver	(387AF)
	✓ Roller blind for windscreen, mechanical	(388AH)
	✓ handles left and right (on B-post)	(389AC)
	✓ handles left and right (on A-post)	(389AD)
	✓ Oddments tray in door armrest	(390AG)
✓ 1 pull-out drawer in centre of dashboard	(390CU)	
✓ Plastic floor and engine tunnel covering	(538AE)	
Instruments	✓ instrument panel kmh 'Base-Line'	(02AAB)
	✓ Digital tachograph, made by CONTI	(042DF)
	✓ calibrate tachograph	(142AF)
	✓ MAN Tronic (on-board computer)	(325AA)
	✓ Language 1 'German' for display in instrument panel	(325EA)
	✓ Language 2 'English' for display in instrument panel	(325FC)
	✓ Display on the dashboard for operating data	(339FP)
	✓ charging pressure indicator	(346CA)
Lights	✓ Beam throw regulator	(309AA)
	✓ Halogen twin headlights H7 for right-hand traffic	(310EE)
	✓ marker lamps	(318AA)
	✓ lateral marker lights	(318AK)
	✓ 2 halogen revolving beacons on cab roof left and right	(352CF)
	✓ Revolving beacon, yellow	(352WS)



**Radio /
Communication
Systems**

✓ Radio MAN BasicLine 24V (350NL)

Electrical System

- ✓ Two-tone horn,electric (324AC)
- ✓ Trailer socket for anti-skid system on frame end (326CK)
- ✓ Trailer socket 24V 7+7-pole on frame end (326CW)
- ✓ Battery main switch, mechanical (327AF)
- ✓ 2 batteries, 12V 175Ah (329CT)
- ✓ Battery box up to 175Ah (329ER)
- ✓ Alternator 28V 80A 2240 W (331CB)

Other

- ✓ opeator's manual in GERMAN (194AD)
- ✓ antifreeze down to -25 degrees (373AD)
- ✓ mudflap front (400AH)
- ✓ synthetic mudguards, 3-part, with mud flaps (401CY)
- ✓ first-aid kit (405AC)
- ✓ hazard-warning sign (405AK)
- ✓ Hazard-warning lamp (405AR)
- ✓ Jack 12 t (407AH)
- ✓ 2 chocks (411AF)

**Operation and
Country-specific
Items**

✓ Fittings for right-hand traffic (600AC)

Without sparetyre

- ✓ Auslieferungspaket: Technische Einweisung im Service-
stützpunkt (nach Übergabe im MAN Kundencenter) (DEA03)
- ✓ MAN Fahrerjacke (DEA04)
- ✓ DTCO personalisieren - Einfügen der Halterdaten, Amt..
Kennzeichen etc. (DEDT1)

**Local additional
equipment:**

- ✓ Umbauarbeiten MAN Landau
- ✓ Überführung MAN Montagewerk - MTS Germersheim



Colours

chassis	✓	9011 graphite black RAL 9011 matt	W
wheels	✓	9006 White aluminium acrylic RAL 9006	N
cab	✓	9010 Pure white RAL 9010	N

Unverbindlicher Liefertermin nach Vereinbarung

Zahlungskonditionen nach Vereinbarung